SOME FACTORS AFFECTING THE INVITRO GAS PRODUCTION OF SOME RUMINANTS FEEDSTUFFS

U. A. Nayel⁽¹⁾, F.M. Abodonia⁽²⁾, B.M. Ahmed⁽¹⁾, E. Sabra⁽³⁾ and M. K. Raslan⁽¹⁾

- (1) Animal production department, Faculty of agriculture, Menoufia University and
- (2) Animal production researches institute, Agriculture researches culture.
- (3) Animal biotechnology department, genetic engineering and biotechnology research institute, Sadat City University.

Received: Feb. 24, 2019 Accepted: Mar. 2, 2019

ABSTRACT: This study was conducted to investigate some factors affecting nutritive value using fermentation gas production technique (Pressure transducer for In-vitro cumulative gas production techniques. Four buffers: (BUF1= MENKE AND STEINGASS (1988). BUF2= GOERING AND VANSEOST (1970. BUF3= THEODORUE (1993). BUF4= STEINGASS (1983)) were used with two different ratios of rumen liquid buffers: (1:2 and 1:3), two different sizes of rumen liquid for incubation (30 ml and 60 ml) , two feedstuffs samples weights (200sw1-600sw2 mg) have been investigated . Various feedstuffs were evaluated: Roughages (rice straw RS), corn stover CS), sugar cane bagasse SCB) and Alfalfa hay AA)). Concentrate (soybean meal SBM) - cotton seed meal CSM) - concentrate feed mix CFM) and corn C)) . Results showed that the highest gas emitted was found with BUF2 (GOERING and VANSEOST (1970) and the lowest was with BUF3 (THEODORUE (1993). Differences were significant (P<0.05). Degradability of OM and NDF followed the same pattern. Rumen liquor size showed significant increase for effective gas production and DM degradability with RL1 (30 ml rumen liquor size); whereas degradability of OM and NDF followed the same pattern. Sample size had no significant effect on gas emitted and the predicted gas production. Degradability of DM, OM and NDF followed the same pattern. The higher effective gas production in concentrate was in high energy source (corn) than that in protein sources. However the highest effective gas production in low quality roughages was reported with AA followed by SCB and RS, while it was least with CS. In general, data revealed that degradability was higher with concentrates than with roughages. With different testing factors.

Key words: In vitro gas production, rumen liquor, buffers, degradability.

INTRODUCTION

Methodology used to measure in vitro gas production has been reviewed to determine impacts of sources of variation on resultant gas production profiles Current methods (GPP). measurement of gas production at constant pressure (e.g., use of gas tight syringes), a system that is inexpensive, but may be less sensitive than others thereby affecting its suitability in some situations. The principle of determining potential rumen degradability/ fermentability of a feed by measuring gas produced from a batch culture was first developed by Hungate (1966). Trei et al. (1970) adapted the earlier techniques by attaching displacement water manometer to each vessel to measure the gas produced. Similarly, Jouany and Thivend, (1986); Beuvink and Spoelstra, (1992) used inverted measuring cylinders to determine the volume of water displaced. Beuvink et al. (1992) then automated this water displacement technique.



Although the pressure transducer technique is a simple approach to estimate fermentation kinetics of a feed, a number of factors in application of the method could potentially affect the gas production profile of any feedstuff. The objective of this review is to consider these sources of variation and assess what impact they have on the GPP, how this variation may be reduced, and how results produced from one laboratory and from one experiment within a laboratory, may be compared with, and extrapolated to, data from laboratories.

MATERIAL AND METHODS

This study was conducted at Rumen Microbiology Laboratory, Animal Production Researches Institute (APRI), Agriculture Researches Center (ARC). and Nutrition Laboratory, Animal **Production** Department, Faculty Agriculture, Menoufia University in order to investigate some factors affecting feeding value using fermentation gas production technique. Four forages (rice straw, corn stover, alfalfa hay and sugar cane bagasse) and four concentrate (concentrate feed mixture, corn, soya bean meal and cotton seed meal) were used. All experimental samples were chopped to pass through a 2mm screen for proximate analysis (Table 1), with tow weight of feedstuffs (200mg sw1 and 600mg sw2).

Four buffers were prepared as media (BUF1= MENKE AND STEINGASS (1988). BUF2= GOERING AND VANSEOST (1970. BUF3= THEODORUE (1993). BUF4= STEINGASS (1983)) and mix with rumen liquor. The composition of solutions is shown in Table (2). Rumen liquor was collected from three rams (approximately weight 40-45kg) by stomach tube. The animals were fed on berseem hay and concentrate feed mixture (CFM 14% CP) at ratio 70:30 (on DM basis). Feed was offered to animals once daily with free

access to fresh water. Rumen fluid was collected from rams and transferred immediately into pre-warmed thermos bottles after strained through two layers of cheese-cloth. Rumen fluid was manipulated under continuous flushing of CO₂. Buffers were mixed with rumen liquor at the ratio of (2: 1) and (3: 1) respectively (buffer to rumen fluid, v/v). A volume of 30 ml of the mixture was added to 200mg of feedstuffs and a volume of 60 ml of the mixture was added to 600mg of feedstuffs at 100ml of dark glasses each glass saturated with CO2 and tightly closed with rubber stopper fitted with outlet valve and incubated at 39°C in a water bath for 72 hours. Glasses were well shaken during all incubation period and the gas volume was recorded after 3, 6, 12, 24, 48, and 72h incubation by pressure transducer for In-vitro cumulative gas production techniques. Three bottles contained the buffer and rumen fluid mixture was included in each run as blank.

The complete chemical composition of the tested feeds was determined according to (AOAC, 2005). Kinetic parameters of gas production (i.e., GP) estimated by fitting GP results (mL/g OM) in the nonlinear regression models (NLIN), option of SAS (2008), according to the model described by France *et al.*, (2000): GP = b × (1 - e^{-c(t-L)})

where: GP is the volume of GP at time t; b is the asymptotic GP (mL/g OM); c is the rate of GP (ml/h) from the slowly fermentable feed fraction b; and L is the lag time prior to GP. Degradability of NDF was estimated according to (Van Soest et al., 1991).

Data of feed intake, degradability, in vitro gas production kinetics, OMD and contents of samples were subjected to the random completely design analysis using General Linear Model (GLM) of SAS (2002). Statistical model applied for analysis was: $Y_{ijk} = \mu + S_i + e_{ijk}$

Table 1: Chemical composition of experimental feedstuffs (on DM basis)

Item%	DM	СР	CF	NFE	EE	ASH
CFM	90.22	13.3	19.23	58.17	4.8	4.5
С	86.5	7.75	2.23	80.22	7.5	2.3
SBM	89.02	38.93	3.88	42.99	7.9	6.3
CSM	90.8	19.68	10.67	53.52	6.53	9.6
RS	89.93	3.25	35.89	40.16	6.7	14
cs	93.05	3.1	32.31	50.99	4.6	9
AA	89.25	8.31	29.14	48.95	4.6	9
SCB	89.9	3.5	30.1	62.9	2	1.5

DM: dry matter, CP: crude protein, CF: crude fiber, NFE: nitrogen free extract, EE: either extract, CFM: concentrate feed mixture(yellow corn, soya bean meal, lime stone, NACL, wheat brain, molas, undecorticated cotton seed meal "solvent extract", C: corn, SBM: soya bean meal, CSM: cotton seed meal, RS: rice straw, CS: corn Stover, AA: AlfaAlfa hay, SCB: sugar cane bagasse.

Table 2: Composition of the media (g/l) used in various gas production techniques

			Media	
Component	Menke and Steingass (1988)	Steingass (1983)	Goering and van Soest (1970)	Theodorou (1993)
CaCl₂·2H₂O	0.013	0.017	0.016	0.015
MnCl ₂ ·4H ₂ O	9.7×10⁻³	0.015	0.012	0.011
CoCl ₃ ·6H ₂ O	0.97×10 ⁻³	0.002	1.25×10⁻³	1.11×10 ⁻³
FeCl ₃ ·6H ₂ O	0.77×10 ⁻³	0.012	9.96×10 ⁻³	8.84×10 ^{−3}
Na ₂ HPO ₄	1.09	1.43	1.42	2.09
KH ₂ PO ₄	1.19	1.55	1.55	1.37
MgSO ₄ ·7H ₂ O	0.12	0.15	0.15	0.13
NaHCO ₃	6.71	8.75	8.74	7.73
(NH ₄)HCO ₃	0.77	1.00	1.00	0.88
Resazurin	9.87×10 ⁻⁴	0.125	1.25×10⁻³	1.11×10 ⁻³
Na ₂ S	0.23	0.52	0.016	2.79×10 ⁻⁴
Trypticase	1.00		2.50	2.21
Cysteine hydrochloride			0.016	2.79×10 ⁻⁴

Where Y_{ijk} represents the general observation of chemical composition, *in vitro* gas production kinetics, OMD, μ is the expected score, S_i is the subject i, S_i effect of tested treatments on the observed parameters and e_{ijk} the standard error term common for all observations. Significant differences among individual means were identified using the Duncan's New Multiple Range Test (1955). Mean differences were considered significant at (P_i <0.05).

RESULTS AND DISCUSSION

Data in Table (3) present the effect of buffer source on gas production; the highest gas emitted was found with BUF2 and the lowest was with BUF3.

Table (4) show that the highest effective gas production and degradability were with BUF2 and the lowest values with BUF3, with significant differences (P<0.05). Degradability of OM and NDF followed the same pattern (Table 3), with significant differences (P<0.05). A number of media have been developed which buffer the incubation and provide relevant micro-nutrients to the microorganisms. Until now, little has been completed relationships between the composition of the medium and measured GP. However, comparing GP from media either rich in N N-free, allows assessment or contributions of Ν containing compounds in the sample. Data in present study revealed that buffer source affects gas production; the highest gas emitted was found with BUF2 and the lowest was with BUF3.

Wilkins (1974) described a different to measure fermentation kinetics in vitro, whereby fermentation took place in a sealed vessel and gas produced was determined using a transducer pressure measure accumulation of pressure in the vessel headspace. This principle of measuring pressure with a sensor or transducer has been widely adopted as a simple, yet method determining sensitive, of fermentation kinetics. The simplest pressure measurement technique requires manual measurement headspace pressure, as described by Theodorou et al. (1994). Semi- and full automation of headspace pressure recording have also been developed, as described by Pell and Schofield (1993), Cone et al., (1996), Mauricio et al. (1998a) and Davies et al. (2000). Whereas Abo-Donia et al. (2015) reported that cumulative gas production was maximum moth (P<0.05) fodder. concentrations of VFAs and NH3-N/ total N were significantly (P<0.05) higher in moth fodder compared to khejri. Also was positive correlation observed between gas production and either OM or NDF disappearance on incubation of moth fodder for 24h compared to khejri.

Table (3): Effect of buffer on gas emitted and gas predicted

Item Gas emitted (ml)						Gas predicted (ml)						
	h3	h6	h12	h24	h48	h72	Ph3	Ph6	Ph12	Ph24	Ph48	Ph72
BUF1	13.61 ^{ab}	24.76 ^b	35.47 ^b	48.26 ^b	62.87 ^b	73.48 ^b	10.56 ^b	22.43 ^b	33.41 ^b	46.61 ^b	61.40°	72.41 ^b
BUF2	14.94ª	27.28ª	39.39 ^a	53.09 ^a	68.62ª	79.49 ^a	12.37ª	25.38ª	37.68ª	51.71ª	67.36ª	78.61ª
BUF3	12.91 ^b	24.07 ^b	35.12 ^b	48.09 ^b	62.52 ^b	72.63 ^b	11.27 ^{ab}	22.85 ^b	34.02 ^b	47.21 ^b	61.72°	72.07 ^b
BUF4	13.94 ^{ab}	25.55 ^{ab}	36.9 ^b	50.10 ^b	64.98 ^b	75.56 ^b	12.30ª	24.34 ^{ab}	35.83 ^{ab}	49.22ab	64.18 ^b	75.01 ^b
±SE	0.46	0.68	0.89	0.90	0.88	1.02	0.46	0.68	0.89	0.90	0.88	1.02

^{*}h = time, Ph =Prediction time, BUF1= MENKE AND STEINGASS (1988). BUF2= GOERING AND VANSEOST (1970), BUF3= THEODORUE (1993), BUF4= STEINGASS (1983), SE= standard error.

a,b, values with different superscript within the same column are significant (P<0.05).

Effective gas production(ml) Degradability(%) Item b C DM OM NDF BUF1 76.71^b 0.042^{a} 45.25b 50.08b 37.44b BUF2 82.22a 0.045a 54.42a 40.69a 49.18a BUF3 75.83^b 0.043a 49.83b 37.26^b 45.02b 78.90^b 46.89ab 38.80ab BUF4 0.043a 51.89^b **±SE** 1.18 0.002 1.16 1.17 1.04

Table (4): Effect of buffer on effective gas production and degradability of DM,OM and NDF

* c= Rate of gas production, b= total gas, DM=dry matter degradability, OM=organic matter degradability, NDF= neutral detergent fiber, BUF1= MENKE AND STEINGASS (1988). BUF2= GOERING AND VANSEOST (1970), BUF3= THEODORUE (1993), BUF4= STEINGASS (1983), SE= standard error., a,b, values with different superscript within the same column are significant (P<0.

Automated GP techniques as an *in vitro* technique, is a simple method, but interactions between fermentation end products, buffering system and amount of gas produced are very complex (Beuvink and Spoelstra, 1992). This method detects and provides useful data on fermentation kinetics of both soluble cell contents and non-soluble fractions of feedstuffs (Getachew *et al.*, 1997). Another advantage with this method is that it can analyze a large number of samples at one time, making the analytical capacity high (Cone *et al.*, 1997).

It is recommended to take the rumen liquor before feeding, because it is most constant in its composition and activity. It is approved to take the rumen fluid mixture from two donor animals at least as the guarantees a greater constancy of activity (Menke et al., 1979; Menke and Steingass, 1988).

Table (5) show that the highest gas emitted was with RL1 and the lowest was found with RL2.

The highest effective gas production was found with RL1 (Table 6) while the lowest was reported for RL2; on the other hand, the highest DM degradability was

found with RL1 and the lowest was with RL2. Degradability of OM and NDF followed the same pattern (Table 6). With significant differences (P<0.05).

Results of Rymer et al., (2005) indicated that there was little effect of rumen liquid preparation on gas production. When Pell and Schofield. (1993) used the next percentage of rumen liquor in all medium (5, 10, 20 and 40%) he found that when the rumen liquor percent was increased the percent of alfalfa hay digestibility was increased with the best rate of maximum fiber digestion was 20%. Rymer et al., (2005) reported that when rumen liquor was increased in the incubation medium, the lag time of gas production was reduced, but the volume or the rate of gas production was increased. It is known that the decrease in rumen liquor to the buffer will decrease the microbial activity; this will lead to reduce the digestibility of feeds.

Results of the effect of sample size on gas emitted presented in Table (7). It was found that sample size had no significant effect on gas emitted. The predicted gas production followed the same pattern of gas emitted.

Table (5): Effect of rumen liquor size on gas emitted and gas predicted

Itom	Gas emitted						Gas predicted					
Item	h3	h6	h12	h24	h48	h72	Ph3	Ph6	Ph12	Ph24	Ph48	Ph72
RL ₁	14.71ª	26.8ª	38.7ª	52.6ª	68.5ª	79.9ª	12.4ª	25.1ª	37.2ª	51.4ª	67.4ª	79.1ª
RL ₂	12.99 ^b	23.95 ^b	34.7 ^b	47.10 ^b	60.92 ^b	70.63 ^b	10.81 ^b	22.35 ^b	33.25 ^b	45.9 ^b	59.8 ^b	69.8 ^b
±SE	0.32	0.47	0.62	0.58	0.58	0.66	0.32	0.47	0.62	0.62	0.58	0.66

^{*}h = time, Ph =Prediction time, RL1= rumen liquor1 (30ml), RL2=rumen liquor 2(60ml), SE= standard error.

Table (6): Effect of rumen liquor size on effective gas production and degradability of DM, OM and NDF

Item	Effective gas	production (ml)	Degradability (%)						
liteiii	В	В С		ОМ	NDF				
RL1	83.67ª	0.042ª	49.47ª	54.75ª	40.93ª				
RL2	68.17 ^b	0.044ª	43.70 ^b	48.36 ^b	36.16 ^b				
±SE	0.76	0.001	0.80	0.80	0.72				

^{*}c= Rate of gas production, b= total gas, DM=dry matter degradability, OM=organic matter degradability, NDF= neutral detergent fiber, RL1= rumen liquor1 (30ml), RL2=rumen liquor 2(60ml), SE= standard error.

Table (7): Effect of samples size on gas emitted and gas predicted

14	Gas emitted(ml)						Gas predicted(ml)					
Item	h3	h6	h12	h24	h48	h72	Ph3	Ph6	Ph12	Ph24	Ph48	Ph72
SS ₁	13.64	25.15	36.43	49.54	64.37	74.86	11.71	23.70	35.13	48.50	63.42	74.20
±SE	0.29	0.43	0.57	0.58	0.58	0.67	0.30	0.43	0.57	0.58	0.58	0.66
SS2	14.20	25.86	37.22	50.47	65.38	76.00	11.50	23.84	35.40	49.01	64.07	75.08
±SE	0.38	0.56	0.74	0.75	0.74	0.86	0.38	0.56	0.74	0.75	0.74	0.86

^{*}h = time of incubation, Ph =Prediction time, SS1= sample size 1 (200mg), SS2=sample size 2 (600mg).

Table (8) presents the effect of sample size (SS) on the effective gas production. It was obvious that no differences were found between both sizes used and the degradability of DM, OM and NDF followed the same pattern (Table 8). Effect of sample preparation on GP has been found to be important whereas using small amount of substrate is prone to experimental error in sample weighing, but further research is required to

determine the optimum preparation that mimics animal chewing. Inoculum is the single largest source of variation in measuring GPP, as rumen fluid is variable and sampling schedules, diets fed to donor animals and ratios of rumen fluid/medium must be selected such that microbial activity is sufficiently high that it does not affect rate and extent of fermentation. Species of donor animal may also cause differences in GP.

a,b, values with different superscript within the same column are significant (P<0.05).

a,b, values with different superscript within the same column are significant (P<0.05).

Effective of gas production (ml) Degradability (%) Item С DM OM NDF В SW1 78.12 0.043 46.37 51.32 38.37 **±SE** 0.76 0.001 0.74 0.75 0.66 SW2 78.91 0.043 46.95 51.95 38.84 0.98 0.001 0.96 0.96 **±SE** 0.86

Table (8): Effect of samples weight on effective gas production and degradability of DM, OM and NDF

Table (8) show that the highest effective gas production with SW2 and the lowest effective gas production with SW1 and highest degradability of dry matter with SW2 and the lowest degradability of dry matter with SW1.

Menke and Steingass (1988) observed that a close correlation between in vitro gas production and digestibility whith the better correlation was achieved when the equation includes crude protein, crude fat and ash content. Blümmel and Ørskov (1993) adapted gas production technique to describe the kinetics of fermentation based on the following exponential model [p=a+b(1-e-cT)] and to predict feed intake in cattle. The results showed that total gas production (a+b) value as described by the equation was correlated with intake (0.88), digestible dry matter intake (0.93) and growth rate (0.95) in a multiple regression model. The use of the rate of gas production c value did not improve the precision of the correlation.

Tuah et al. (1996) evaluating several local Ghanaian foodstuffs and found a positive and significant correlation (0.58 to 0.95) between in sacco DM degradability and in vitro gas production.

Table (9) show that gas emitted from corn (high energy source) at almost all times of incubation was less than that

emitted from protein sources (SBM, CSM and CFM); however, within the roughage sources alfalfa hay revealed the highest gas production. Also data of gas predicted followed the same pattern (Table 9). The highest gas production from roughages was lower than that emitted from concentrates.

The by-products poor in fiber and rich in sugars are quickly degraded by the rumen microbes (Montcho et al., 2017). Menke et al., (1979) observed that there is a high correlation between the amount of substrate and the gas produced over time. It is suggested that no more than 200mg of dry matter of sample should be used, but if it is poorly digestible, it could be 300g. The in vitro assay of foodstuffs in rumen fluid requires a careful drying (Menke and Steingass, 1988).

Generally speaking, it is obvious that gas production up to 24h of incubation was higher with concentrates that with roughages either emitted or predicted. It is well known that concentrate are fermented faster than the roughages thus that lead to more gas production at early time with concentrates while with roughages more gas production was obtained at the late time of incubation. Mertens, (1998) indication that the higher-fiber diets produce gas more than the lower-fiber diets which can mean that

^{*} c= Rate of gas production, b= total gas, DM=dry matter degradability, OM=organic matter degradability, NDF= neutral detergent fiber, SW1= sample weight 1 (200mg), SW2=sample weight 2 (600mg).

acetate production would be more with high-fiber diet, where fermentation of fiber acetate primarily generated and gas is produced when substrate is fermented to generate acetate or butyrate rather than propionate. The quantity of gas produced from the in vitro incubation of a substrate is closely related to its digestibility and consequently to its energetic value (Menke et al., 1979; Menke and Steingass 1988). The gas production data may provide a prediction the effective organic of matter degradation in sacco (Deaville and Givens, 1998a). Van Larr et al. (1998) found differences fermentation in hull characteristics between endosperm of full fat Soya beans; this is possibly related to the polysaccharide composition, mainly the differences in cellulose, hemicellulose and pectin concentration in each fraction. This work pointed out the necessity to assess the different vegetal fractions in a sample.

Table (10) show that the highest effective gas production was in concentrate with high energy (corn) than that with protein; the highest effective gas production in low quality roughages was reported with AA followed by SCB and RS while it was least with CS.

general, data revealed that degradability was higher with concentrates than with roughages. Within concentrate sources degradability of OM was highest with protein sources (SBM and CSM) while within roughages it was highest with AA than the other sources.

Table (9): Effect of feedstuffs on gas emitted and gas predicted

14			Gas e	mitted			Gas predicted						
Item	h3	h6	h12	h24	h48	h72	Ph3	Ph6	Ph12	Ph24	Ph48	Ph72	
Conc	Concentrate												
SBM	18.74a	31.7b	42.2b	53.8c	63.9d	70.8d	16.5a	30.4b	40.7b	52.6c	62.1d	70.0d	
CSM	17.bc	29.6c	37.7d	47.4e	55.7e	63.2f	15.bc	28.0c	36.2d	46.2e	54.6e	62.4f	
CFM	17.9b	34.4a	49.21a	61.76a	72.4b	80.8b	15.7b	32.7a	47.7a	60.5a	71.4b	80.0b	
С	16.9c	27.2d	40.51c	50.6d	61.3d	75.8c	14.7с	25.6d	39.0c	49.4d	60.2d	75.0c	
Avg	17.7a	30.7a	42.42a	53.4a	63.2b	72.6b	15.5a	29.1a	40.9a	52.2a	62.1b	71.9b	
Roug	hages												
AA	14.37d	26.3e	41.2bc	58.4b	76.5a	89.8a	12.1d	24.5e	39.7bc	57.2b	75.4a	89.0a	
cs	7.92f	16.0h	22.5g	37.3g	5 7.8e	67.9e	5.7f	14.3h	21.0g	36.1g	56.7e	67.1e	
RS	8.40f	17.6g	27.5f	40.7f	62.3d	73.3cd	6.1f	16.0g	26.1f	39.5f	61.2d	72.5cd	
SCB	9.09e	20.3f	32.7e	48.8de	68.4c	80.4b	6.8e	18.6f	31.2e	47.6de	67.3c	79.7b	
Avg	9.95b	20.0b	31.0b	46.3b	66.2a	77.9a	7.7b	18.4b	29.5b	45.13b	65 .1a	77.1a	

^{*}h = time of incubation, Ph =Prediction time, SBM, soya bean meal; CSM, cotton seed meal; CFM, concentrate feed mix; C, corn; AA, Alfalfa hay; CS, corn Stover; RS, rice straw; SCB, sugar cane bagasse.

a,b, values with different superscript within the same column are significant (P<0.05).</p>

Table (10): Effect of feedstuffs on effective gas production and degradability of DM, OM and NDF

Item		ive gas tion (ml)	Degradability (%)				
	В	С	DM	ОМ	NDF		
Concentrates							
SBM	68.38e	0.06 ^b	59.97ª	66.98ª	52.36ª		
CSM	60.95 ^f	0.06°	57.07 ^b	61.24 ^b	51.48ª		
CFM	77.05 ^d	0.07ª	54.96°	57.62°	47.49 ^b		
С	76.64 ^d	0.04 ^d	54.50°	59.00°	29.28°		
Avg. (concentrates)	70.75 ^b	0.06ª	56.62ª	61.21ª	45.15ª		
Roughages							
AA	92.71ª	0.04 ^d	44.49 ^d	49.57 ^d	36.19°		
cs	81.57°	0.02 ^g	34.61e	41.71e	31.70 ^d		
RS	84.25 ^{bc}	0.03 ^f	33.85°	37.25 ^f	30.96 ^d		
SCB	85.78 ^b	0.03e	33.43°	39.06 ^f	28.93 ^e		
Avg. (Roughages)	86.08ª	0.031 ^b	36.55 ^b	41.90 ^b	31.94 ^b		
±SE	1.03	0.001	0.62	0.70	0.55		

^{*}h = time of incubation, Ph =Prediction time, SBM, soya bean meal; CSM, cotton seed meal; CFM, concentrate feed mix; C, corn; AA, Alfalfa hay; CS, corn Stover; RS, rice straw; SCB, sugar cane bagasse.

Khazaal et al. (1993) correlated chemical composition (i.e. CP, NDF, ADF or ADL) with *in vitro* two-stage digestibility, in sacco degradability and gas production with voluntary intake and in vivo apparent DM digestibility of 10 graminaceous hays in sheep. Accurate prediction of intake and in vivo apparent DMD were achieved using NDF, ADF, ADL, and CP in multiple regression. However, using the (a + b and c) of gas production only intake was predicted accurately. The lower performance of the gas test was attributed to the small contribution to gas production and higher buffering capacity resulting from protein fermentation.

In vitro cumulative gas production techniques were developed to predict fermentation of ruminant feedstuffs. A feedstuff is incubated with buffered rumen fluid as soon as gas produced is measured as an indirect indicator of fermentation kinetics. When a feedstuff is incubated with buffered rumen fluid, it is first degraded and the degraded fraction may either be fermented to produce gas and fermentation acids, or incorporated into microbial biomass. When combined with measures of degradation, techniques provide production measure of the proportion of feed that is fermented as opposed to that which is partitioned to microbial growth.

a,b, values with different superscript within the same column are significant (P<0.05).

From a historical point of view the in vivo method has generated a lot of important knowledge about fermentation for different types of feeds (Kitessa et al., 1999). This method will also be important in the future, because in vivo trials will be needed as it represents the actual animal response to a dietary treatment. In the system published by Menke et al. (1979) the substrate was incubated in a calibrated gas-tight glass syringe fitted with a plunger, the gas produced over 96 h period is recorded. The incubation media include rumen liquor and a buffer. The main innovation in such method was that the gas production is recorded rather than degradation. The same postulate continues until today, even when the method had been simplify and improved.

The most negative aspect with this method is that it requires donor animals to supply rumen fluid, which is materially expensive (Kitessa et al., 1999). Another limitation with the GP technique is that it has a lack of standardization in the methodology, which makes it difficult to make comparisons on results between different laboratories (Williams, 2000).

Where it appeared that the dried negatively arass affects the production profile (Rymer and Givens, 1998). Nagadi et al., (1998) observed that the gas production profile of dried Festuca rubra for 20 h at 65°C is more closely associated with that of the fresh sample when milling is completed through 0.4 mm Sieve as compared to 1.0 mm. Van Larr et al., (1998) found fermentation differences in characteristics between hull and endosperm of full fat Soya beans; this is possible related to the polysaccharide composition, mainly the differences in cellulose. hemicellulose and concentration in each fraction. Gas production rate was increased when particle size was decreased in fibrous feeds. Rymer et al., (2005) indicated that maize grain that was steam-flaked, rolled or left intact had the same rate and extent of gas production when it was ground through a 1-mm screen but not when it had been ground through a 4-mm screen.

REFERENCES

- A.O.A.C. (2005). Official Methods of Analysis, Association of Official Analytical Chemist, Washington DC
- Abo-Donia, F.M. and A.K. Nagpal (2015). in Vitro Evaluation of Moth (Phaseolus aconitifolius) Fodder, Khejri (Prosopis cineraria) Leaves and Their Combinations in Camel. Indian J. Anim. Nutr32.2.p192-197.
- Beuvink, J. M. W., S. F. Spoelstra and R. J. Hogendorp (1992). An automated method for measuring time-course of gas production of feedstuffs incubated with buffered rumen fluid. Neth. J. Agric. Sci., 40:401-407.
- Beuvink, J.M.W and S.F. Spoelstra (1992). Interactions between substrate, fermentation end-products, buffering systems and gas production upon fermentation of different carbohydrates bγ mixed rumen microorganisms in vitro. Appl. Microbiol. Biotechnol. 37(4):505-9.
- Blümmel, M. and E. R. Ørskov (1993). Comparison of gas production and nylon bad degradability of roughages in predicting feed intake in cattle. Anim. Feed Sci. Technol. 40:401-407.
- Cone, J.W., A.H. van Gelder, G.J.W. Visscher and L. Oudshoorn (1996). Influence of rumen fluid and substrate concentration on fermentation kinetics measured with fully а automated time related gas production apparatus. Anim. Feed Sci. Technol. 61, 113-128.
- Cone, J. W., A. H. van Gelder and F. Driehuis (1997). Description of gas production profiles with a three-

- phasic model. Anim. Feed Sci. Technol. 61:31-45.
- Davies, Z.S., D. Mason, A.E. Brooks, G.W. Griffith, R.J. Merry and M.K. Theodorou (2000). An automated system for measuring gas production from forages inoculated with rumen fluid and its use in determining the effect of enzymes on grass silage. Anim. Feed Sci. Technol. 83, 205–221.
- Deaville, E. R. and D. I. Givens (1998a). Investigation of direct gas production from silage fermentation acids. Proceedings of the British Society of Animal Science. Scarborough, March 1998. p. 64.
- Duncan, D. B. (1955). Multiple range and multiple F test J. Biometrics 11:1.
- France, J., J. Dijkstra, M.S. Dhanoa, S. Lopez and A. Bannink (2000). Estimating the extent of degradation of ruminant feeds from a description of their gas production profiles observed *in vitro*: derivation of models and other mathematical considerations. Brit. J.I of Nutr. 83, 143–150.
- Getachew, G., M. Blümmel, H. P. S. Makkar and K. Becker (1997). *In vitro* gas measuring techniques for assessment of nutritional quality of feeds: a review. Anim. Feed Sci. Technol. 72:261-281.
- Hungate, R.E. (1966). The rumen and its microbes. New York, NY, USA: Academic Press.
- Jouany, J.P. and P. Thivend (1986). *In vitro* effect of avoparcin on protein degradability and rumen fermentation. Anim. Feed Sci. Technol. 15, 215–229.
- Khazaal, K., M. T. Denthino, J. M. Ribeiro and E. R. Ørskov (1993). A comparison of gas production during incubation with rumen contents *in vitro*.
- Kitessa, S., P. C. Flinn and G. G. Irish (1999). Comparison of methods used to predict the in vivo digestibility of

- feeds in ruminants. Aus. J. Agric. Res. 50:825-841.
- Mauricio, R. M., A. L. Abdalla, F. L. Mould, U. R. Altaf, T. Smith, E. Owen, D. I. Givens, M. S. Dhaona and M. K. Theodorou (1998a). Comparison of bovine rumen liquor and faeces as source of microorganisms for the in production technique vitro gas assessed using twelve graminaceous forages. Proceedings of the British Society Animal Science. of Scarborough, March 1998. p. 68.
- Menke, K., Raab, A. Salewski, H. Steingass, D. Fritz and Schneider, W. (1979). The estimation of the digestibility and metabolizable energy content of ruminant feeding stuffs from the gas production when they are incubated with rumen liquor in vitro. J. Agric. Sci. (Camb.) 93, 217–222.
- Menke, K.H. and H. Steingass (1988). Estimation of the energetic feed value obtained from chemical analysis and gas production using rumen fluid. Anim. Res Dev. 28:7–55.
- Mertens, D. R. (1998). Nutritional properties of carbohydrates in feeds and their roles in dairy rations. Pages 85–99 in Proc. 19th Western Canada Nutr. Conf., Univ. Saskatchewan, Saskatoon, Canada.
- Montcho, M., S. Babatiunde, A. B. Aboh, V. Bougouma-Yameogo and G. A. Mensah (2017). *In vitro* digestibility and fermentation kinetics of agroindustrial by-products used in ruminal feeding in Benin Republic. J. Applied. Bioscience. 116: 11628–11640.
- Nagadi, S., M. Herrero and N. S. Jessop (1998). A comparison of the gas production profiles of fresh and dry forage. Proceedings of the British Society of Animal Science. Scarborough, March 1998. p. 62.
- Pell, A.N. and P. Schofield (1993). Computerized monitoring of gas

- production to measure forage digestion *in vitro*. J Dairy Sci. 76 (4): 1063 –73.
- Rymer, C. and D. I. Givens (1998).
 Relationship between the rates of production of gas and VFA during in vitro incubations of high temperature dried grass. Proceedings of the British Society of Animal Science. Scarborough, March 1998. p55.
- Rymer, C., J.A. Huntington, B.A. Williams and D.I. Givens (2005). *In vitro* cumulative gas production techniques: history, methodological considerations and challenges. Anim. Feed Sci. Technol. 123-124(1):9–30.
- SAS Institute Inc. (2002). JMP 5 Statistical Software. NC, USA: Cary.
- SAS Institute Inc. (2008). SAS/STAT Software, version 9.2. SAS
- Theodorou, M.K., B.A. Williams, M.S. Dhanoa, A.B. McAllan and J. France (1994). A simple gas production method using a pressure transducer to determine the fermentation kinetics of ruminant feeds. Anim. Feed Sci. Technol. 48 (3–4):185–97.
- Trei, J., W. Hale and B. Theurer (1970). Effect of grain processing on *in vitro* gas production. J. Anim. Sci. 30, 825–831.

- Tuah, A. K., D. B. Okail, E. R. Ørskov, D. Kyle, W. Shand, J. F.D. Greenhalgh, F. Y. Obese and P. K. Karikari (1996). In sacco dry matter degradability and in vitro gas production characteristics of some Ghanaian Feeds. Livestock Research for Rural Development, Vol. 8, No. 1, January 1996. pp. 23-33.
- Van Larr, H., S. Tamminga, B. Willians, B. Diekema, W. Burgers, D. Groeneveld and M. Hoogendoorn (1998). *In vitro* fermentation characteristics of Soya bean cell wall separated from hulls and endosperm. Proceedings of the British Society of Animal Science. Scarborough, March 1998. p. 71.
- Van Soest, P. J., G. B. Robertson and B. A. Lewis (1991). Methods for dietary fiber, neutral detergent fiber, and non-starch carbohydrates in relation to animal nutrition. J. of Dairy Sci, 74, 3583–3597.
- Wilkins, J. (1974). Pressure transducer method for measuring gas production by microorganisms. Appl. Microbiol. 27, 135–140.
- Williams, B.A. (2000). Cumulative gas production techniques for forage evaluation. In: Givens DI, Owen E, Axford RFE, Omed HM, editors. Forage evaluation in ruminant nutrition. Wallingford: CABI Publishing; p. 189–213.

بعض العوامل المؤثرة على انتاج الغاز معمليا في بعض اغذية المجترات

أسامة أبو العز نايل^(۱)، فوزى محمد أبو دنيا^(۱)، بركات محمد أحمد^(۱)، إبراهيم صبرا^(۱) ، محمد خالد رسلان^(۱)

- (١) قسم الانتاج الحيواني كلية الزراعة جامعة المنوفية
- (١) معهد بحوث الإنتاج الحيواني مركز البحوث الزراعية وزارة الزراعة
 - (٣) معهد الهندسة الوراثية مدينة السادات

الملخص العربي:

اجريت هذه الدراسة لتقييم بعض العوامل المؤثرة على القيمة الغذائية عن طريق قياس انتاج الغاز بالطريقة المعملية باستخدام جهاز (Pressure transducer for *In-vitro* cumulative gas production techniques) تم استخدام المنظمات الأتية:-

- BUF1= MENKE AND STEINGASS (1988)-1 (المنظم الأول)
- BUF2= GOERING AND VANSEOST (1970)-2 (المنظم الثاني)
 - BUF3= THEODORUE (1993)-3 (المنظم الثالث)
 - BUF4= STEINGASS (1983)-4 (المنظم الرابع)

استخدمت نسب خلط مختلفة من سائل الكرش بالمنظمات (۲:۱ و ۳:۱) على الترتيب وأحجام مختلفة من سائل الكرش المعد للتحضين واختبرت أوزان مختلفة لعينات مواد العلف وكانت الاوزان (۲۰۰ – ۲۰۰ مجم على الترتيب) كذلك تم استخدام ۳۰ مل و ۲۰ مل على الترتيب (سائل الكرش بالمنظمات)

تم تقييم مواد علف مركزة ومالئة مختلفة كالتالي :-

مواد علف خشنة (قش الارز - حطب الذرة - مصاصة القصب - دريس البرسيم)

مواد علف مركزة (كسب فول الصوبا - كسب بذرة القطن - ذرة صفراء -علف مصنع).

وأظهرت نتائج الدراسة ما يلى:

- ١- تأثير مصدر المنظم: سجلت أعلى كمية غاز منبعثة وكذلك اعلى معدل هضم للمادة الجافة عند استخدام المنظم (1970) Van Soest (1970).
 وكانت الاختلافات معنوية, واتبعت معاملات هضم المادة العضوبة والألياف المتعادلة نفس المنوال.
- ٢- بدراسة تأثير حجم سائل الكرش المعد للتحضين على الغاز المنبعث وجد أن استخدام ٣٠ مل من سائل الكرش أحدث زيادة معنوية ف انتاج الغاز مقارنة ب ٢٠ مل , كما سلكت معاملات هضم كلا من المادة الجافة والمادة العضوية والالياف المتعادلة نفس النمط.
- ٣-تاثير وزن العينة: لم يكن هناك تأثير معنوى لوزن العينة على كلا من حجم الغاز المنبعث او المتنبأ بانبعاثة واظهرت معاملات هضم المادة العضوبة والألياف المتعادلة نفس المنوال.
- خ-حجم الغاز المنبعث مع الذرة (كمصدر غنى بالطاقة) فى جميع أوقات التحضين كان أقل مقارنة بمصادر البروتين
 (كسب فول الصوبا كسب القطن العلف المركز).
- عند مقارنة مواد العلف الخشنة سجل دريس البرسيم الحجازى اكبر حجم من الغاز تبعه كلا من مصاصة القصب وقش
 الأرز على الترتيب في حين كانت حطب الذرة الاقل قيمة .
 - ٦- يمكن استنتاج من نتائج الدراسة ارتفاع معاملات هضم مواد العلف المركزة مقارنة بالمواد المالئة.

السادة المحكمين

أ.د/ هانم عبدالرحمن الشيخ مركز البحوث الزراعية - القاهرة ، أ.د/ جمال أحمد براغيت كلية الزراعة - جامعة المنوفية