



Answer the following questions. Use of steam and gas tables and charts is allowed.
Assume any necessary assumptions. Mark

Steam Turbines

1. a) How are steam turbines classified? Give a list of the types of steam turbines. 6
- b) A steam turbine plant employing regenerative feed heating has the following data: 14
Steam conditions at inlet $p=85$ bar, $t=520$ °C
Condenser pressure= 0.042 bar
Bleed points are at pressures 15,10.5 and 0.8 bar. The efficiencies of expansions between various pressures are 85%, 80% , 79% and 70% respectively. Draw a schematic of the plant and the T-S diagram of the cycle, and determine:
i) the final state of steam after expansion,
ii) mass of steam raised in the boiler per kg of steam condensed in the condenser,
iii) improvement in the thermal efficiency and heat rates due to feed heating, and
iv) decrease of steam flow to the condenser per kWh due to feed heating.
- c) A combined gas and steam plant develops 10 MW at a gas turbine shaft with an efficiency of $\eta_{gt}= 22\%$. A steam turbine power plant ($\eta_{st}=33\%$) is operated through the WHRB which receives the turbine exhaust, calculate: 10
i) The output of steam turbine plant,
ii) The thermal efficiency of the combined cycle plant,
iii) The overall heat rate.
2. a) Drive the following relations: 10
 $\sigma_{opt}= 0.5 \sin\alpha_2$, $\epsilon_{max}= \sin^2\alpha_2$, and $w_{st}= 2u^2$. For single-stage impulse turbine.
- b) The initial pressure and temperature of steam entering a single stage impulse turbine ($d=1$ m, $N=3000$ rpm and $\eta_{st}=85\%$) are 100 10

bar and $550\text{ }^{\circ}\text{C}$ respectively. The steam flow rate is 100 kg/s and exit angle of the nozzle blades is 70° . Assuming maximum utilization factor, determine the rotor blade angles, blade height, power developed and the final state of steam after expansion.

Gas Turbines

3. a) Classify briefly types of turbomachines. 8
b) Draw carefully each of block diagram and temperature-entropy chart for an intercooled- regenerative-gas turbine cycle. Explain briefly the function of each component of the cycle.
4. A heat exchanger gas turbine engine is operating under the following conditions: Compressor inlet pressure and temperature = 100 kPa and $27\text{ }^{\circ}\text{C}$, respectively. The compressor pressure ratio = 8 and the turbines inlet temperature = $1127\text{ }^{\circ}\text{C}$. Compressor and turbine polytropic efficiencies = 85% and 90% , respectively. The effectiveness of the heat exchanger = 85% . Assume air mass flow rate = 50 kg/s , low calorific value of the used fuel = 44 MJ/kg , the combustion efficiency = 99% , constant specific heats and the stagnation-pressure losses = 6% , calculate;
a) The power developed
b) The used fuel mass flow rate
c) The thermal efficiency of the engine cycle. 20
5. A turbojet engine is operating under the following conditions: Altitude = 12 km . Mach number = 1.2 . Pressure ratio across the compressor = 18 . Temperature at turbine inlet = 1300 K . The diffuser pressure recovery ratio = 80% and the efficiencies of the compressor, the turbine and the nozzle are; 88% , 90% and 95% , respectively. Air enters the compressor at a rate of 40 kg/s , and the jet fuel has low heating value = 44 MJ/kg . Draw carefully the temperature-entropy chart and for average specific heats calculate each of;
a) The thrust developed. 22
b) The propulsive efficiency.
c) The rate of fuel consumption.
d) The thrust specific fuel consumption

Good luck,

Prof. Dr. S. H. El-Emam, Dr. A. Abd Elsalam

Z	Probability of completing by Ts	Z	Probability of completing by Ts
-3.0	0.00	+0.1	0.54
-2.5	0.01	+0.2	0.58
-2	+0.02	+0.3	0.62
-1.5	0.07	+0.4	0.66
-1.4	0.08	+0.5	0.69
-1.3	0.10	+0.6	0.73
-1.2	0.12	+0.7	0.76
-1.1	0.14	+0.8	0.79
-1.0	0.16	+0.9	0.82
-0.9	0.18	+1.0	0.84
-0.8	0.21	+1.1	0.86
-0.7	0.24	+1.2	0.88
-0.6	0.27	+1.3	0.90
-0.5	0.31	+1.4	0.92
-0.4	0.34	+1.5	0.93
-0.3	0.38	+2.0	0.98
-0.2	0.42	+2.5	0.99
-0.1	0.46	+3.0	1.00
0.0	0.50		